



# Metal Primer WB

## Product description



Metal Primer WB is a water-based anti-corrosion primer based on a specially developed modified alkyd resin. The product also contains anti-corrosion pigments such as zinc phosphate. Thanks to its unique composition, Metal Primer WB has the following properties:

- Good adhesion to steel, prepainted steel sheets, etc.
- Effective corrosion protection
- Fast drying
- Rapid achievement of water resistance  
– after about 4 hours' drying at 20° C
- Can be treated with water-based paints such as Isonit roof coating (all types and glosses) and solvent-based coatings such as Metal Topcoat.

## Use



Metal Primer WB can be used on steel sheets and steel prepainted facade sheets (such as plastisol-coated sheets). The product can be used to prime steel for general indoor and outdoor use. Before applying Metal Primer WB, the surface should be cleaned thoroughly using a pressure washer to remove all dirt, grease, loose rust and paint. During periods with low temperatures below 10° C, Metal Primer is not recommended.

**Please make a test to ensure compatibility with the surface.**

## Technical data



**Type:** Water-based modified alkyd **Colour:** Pale grey and Oxide red **Thinning:** If necessary with water, max. 5% **Coverage:** 8-12 m<sup>2</sup>/litre **Application method:** Brush, roller or spray **Coat thickness:** Recommended: Wet film 100 microns Dry film 40 microns **Gloss Value:** Approx. gloss 5-matt **Specific Gravity:** Approx. 1.3 kg per litre **Drying Time:** Tack free after about 1 hour at 20°C. Recoat after about 1-2 hours at 20°C. Lowest application and hardening temperature +10°C. **Storage:** Store dry and frost-free. Keep out of reach of children. **VOC:** Max 30 g/l (Cat A/g)

## Benefits


**Anti-corrosion primer**

**Based on zinc Phosphate and covering pigments**

**Good adhesion to steel**

**Effective corrosion protection**

**Water based**



**Iso Paint Nordic A/S**  
Tvaervej 8  
6640 Lunderskov  
Denmark

Phone +45 7633 3114  
Fax +45 7633 3115

mail@isopaint.com  
www.isopaint.com



ISO PAINT NORDIC A/S