

# Rubber Roof Coating



## Product description



Rubber roof coating is a special thick film coating, which has a massive rubber look consistence, when it is dry. To be used where the roof is either very damaged or leaky.

It has the ability to be put on in a very thick layer on almost every foundation like; asbestos cement, concrete, asphalt paper, tile, wood, cast, metal etc. It also contains parts against growth, and is added UV – absorbants Furthermore the Rubber roof coating is very elastic and can be stretched for 500-700 % the coating keeps its elasticity down to minus 20 °C

## Use



Rubber roof coating is applied on the clean surface with a brush, roller, or spray. It is important to apply plenty of coat, especially if the roof, is leaky or very damaged. If the foundation is very bad; it would be of great advantage to use a net as foundation. This must be dipped in wet paint and applied 1 or 2 layers of Rubber coating. It is important to let the first layer dry completely before the next treatment.

You will achieve the best result by spraying.

**Please make a test coat of the surface for controlling the capability.**

## Technical data



**Colour:** Black, anthracite grey, grey, tile red, brown, mocca **Dilute:** If necessary with water **Coverage:** App. 3 m<sup>2</sup> per lt. **Applications method:** Brush, roller, or spray **Gloss:** App. 10 **Dry matter content:** App. 65 w/w % **Drying time:** App. 1-2 hours at 20 °C, depending on the thickness of the painting, tem perature, RH coat **Second coat:** Second painting/applying must not happen before the first applying has hardened after app.24 hours **Storage:** Dry, non-freezing, out of reach to children **Cleaning:** Tools etc. are cleaned in water

## Benefits

### Thick film coating

**It has the ability to be put on in a very thick layer**

**Very elastic and can be stretched for 500-700 %**

**Keeps its elasticity down to minus 20 °C**

**For leaky and damaged roofs**



**Iso Paint Nordic A/S**  
Tvaervej 8  
6640 Lunderskov  
Denmark

Phone +45 7633 3114  
Fax +45 7633 3115

mail@isopaint.com  
www.isopaint.com



**DANAK**  
Quality &  
Environmental system  
according to  
**DS/EN ISO 9001**  
**DS/EN ISO 14001**  
by  
Det Norske Veritas,  
Danmark A/S  
Certification Dept.



**ISO PAINT NORDIC A/S**